

HUBER+SUHNER® DATA SHEET

Coaxial Cable: SUCOFORM_86_FEP



Description

SUCOFORM, the handformable microwave cable with protective jacket

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Wire	0.53 mm
Dielectric	PTFE		1.65 mm
Outer conductor	Copper, Tin plated	Tin soaked braid, 100 %	2.1 mm
Jacket	FEP	RAL 3027 - rd	2.5 mm +/- 0.1
Print	HUBER+SUHNER SUCOFORM 86 FEP 50 Ohm (Pa no.)		

Electrical Data

Impedance	50	Ω +/- 2
Max. operating frequency	40	GHz
Capacitance	95	pF/m
Velocity of signal propagation	71	%
Signal delay	4.7	ns/m
Insulation resistance	$\geq 1 \times 10^8$	M Ω m
Min. screening effectiveness	>100	dB (up to 18 GHz)
Max. operating voltage	1.5	kV _{rms} (at sea level)
Test voltage	3	kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.8	kg/100 m
Min. bending radius	static	6 mm
	repeated (for max. 50 bendings)	20 mm

Environmental Data

Temperature range	-20 °C... + 60 °C	-65 °C... + 165 °C
Installation temperature	-20 °C... + 60 °C	
Flammability	IEC 60332-1, UL 1581 § 1080 (VW-1)	
2002/95/EC (RoHS)	compliant	

Ordering Information

Order as SUCOFORM_86_FEP

Additional Information

Remarks

(For details refer to the HUBER+SUHNER MICROWAVE CABLES AND ASSEMBLIES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	crimped (Y3)
	clamped (Y11)
	soldered —

HUBER+SUHNER® DATA SHEET

Coaxial Cable: SUCOFORM_86_FEP



Rev.: L

Matrix **Attenuation** [formula: $(a \cdot f^{0.5} + b \cdot f)$] **and Power CW** [formula: $(p \cdot f^{0.5})$]

Coefficients:

a=	0.6283	b=	0.04	f _{max} =	40	p _{at} 1GHz =	280
	Frequency		Nom. attenuation		Nom. attenuation		Max. CW power
	(GHz)		(dB / m)		(dB / ft)		(watt)
			sea level 25° C ambient temperature		sea level 25° C ambient temperature		sea level 40° C ambient temperature
	2.0		0.97		0.296		198
	4.0		1.42		0.433		140
	6.0		1.78		0.543		114
	8.0		2.10		0.640		99
	10.0		2.39		0.728		89
	12.0		2.66		0.811		81
	14.0		2.91		0.887		75
	16.0		3.15		0.960		70
	18.0		3.39		1.033		66
	20.0		3.61		1.100		63
	22.0		3.83		1.167		60
	24.0		4.04		1.231		57
	26.0		4.24		1.292		55
	28.0		4.44		1.353		53
	30.0		4.64		1.414		51
	32.0		4.83		1.472		49
	34.0		5.02		1.530		48
	36.0		5.21		1.588		47
	38.0		5.39		1.643		45
	40.0		5.57		1.698		44

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
 www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions